

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows, noting that all pending, non-withdrawn claims are included herein for the convenience and efficiency of examination, and that only those claims so indicated as amended are being amended herein:

1. (Currently Amended) A positive temperature coefficient of resistance current limiting assembly comprising:

a positive temperature coefficient of resistance current limiting device having a body having a socket ~~therein~~ in a side thereof, a capacitor disposed on the same side of said body as said socket and a positive temperature coefficient of resistance resistor,

at least one male conductive terminal in the socket of the body for receiving ~~the corresponding~~ a female conductive connection element on the an electrically isolated plug, ~~said socket being adapted to receive a connection end of an said electrically isolated plug~~, said plug-having a female conductive connection element within an insulating open-ended sheath, said socket being adapted to receive the female connection element and at least a portion of said open-ended sheath, and

said male conductive terminal having an end disposed in the socket below said side and being inside said socket sufficiently so that when said electrically isolated plug is fully received into said socket and said female conductive connection element received onto said male conductive terminal, at least a portion of said sheath is inside said socket; and

an engagement member on the body of the positive temperature

coefficient of resistance current limiting device.

2. (Currently Amended) The assembly of Claim 1, ~~further comprising a~~ wherein the capacitor ~~having~~ has at least one male connector and there is at least one female receptacle on the positive temperature coefficient of resistance current limiting device for receiving the at least one male connector of the capacitor.

3. (Previously Presented) The assembly of Claim 1 wherein the electrically isolated plug further comprises a flexible arm with a locking tab of a size and shape such that the upper surface of the locking tab can be retainingly secured against the underside of the engagement member.

4. (Previously Presented) The assembly of Claim 3 wherein the flexible arm can be flexed so as to release the locking tab from pressing up against the underside of the engagement member.

5. (Previously Presented) The assembly of Claim 1, wherein the male connection terminal in the socket on the positive temperature coefficient of resistance current limiting device is electrically isolated from adjoining conductive parts when said electrically isolated plug is fully received into said socket and said female conductive connection element received onto said male conductive terminal with at least a portion of said sheath inside said socket.

6. (Previously Presented) The assembly of Claim 1, wherein there are at least two sockets and at least two respectively corresponding male terminals, each of the two sockets on the positive temperature coefficient of resistance current limiting device being

of a different size to fit different sized plugs to facilitate connection of the correct plug to the correct male conductive terminal.

7. (Previously Presented) The assembly of Claim 1, wherein the male conductive terminal is attached to at least one plate made of conductive material.
8. (Previously Presented) The assembly of Claim 1, wherein the male conductive terminal is attached to at least one plate made of conductive material by means of welding.
9. (Previously Presented) The assembly of Claim 1, wherein the male conductive terminal is attached to at least one plate made of conductive material by means of soldering.
10. (Currently Amended) The assembly of Claim 1 wherein said at least one male conductive terminal is attached to a portion of a plate from which a previously existing male conductive terminal has been cuttingly removed.
11. (Withdrawn) A method for connecting a positive temperature coefficient of resistance resistor/overload device to electrically conductive wire, the method comprising:
 - providing a positive temperature coefficient of resistance resistor/overload device with at least one male conductive terminal connected to a plate protruding from a socket, and an angle protruding outwardly from the body of the positive temperature coefficient of resistance resistor/overload device in a plane parallel to the top of the device adjacent to the at least one socket;

attaching a plug assembly with at least one female conductive element, and at least one electrically isolated female wire receptacle for receiving electrical wire to the electrically conductive wire; and

inserting the plug assembly into the positive temperature coefficient of resistance resistor/overload device such that the at least one female conductive element on the plug assembly is fittingly engaged on the corresponding male conductive terminal in the socket on the positive temperature coefficient of resistance resistor/overload device.

12. (Withdrawn) The method of Claim 11 further comprising connecting a capacitor having at least one male connector into an at least one electrically isolated female receptacle for receiving the capacitor on the positive temperature coefficient of resistance resistor/overload device.

13. (Withdrawn) The method of Claim 11 further comprising lockingly engaging the topmost surface of a locking tab on a flexible arm on the plug assembly under the underside of the angle on the positive temperature coefficient of resistance resistor/overload device.

14. (Withdrawn) The method of Claim 13 further comprising flexing the flexible arm so as to release the locking tab from pressing up against the underside of the angle.

15. (Withdrawn) The method of Claim 11 further comprising making each male conductive element socket on the positive temperature coefficient of resistance resistor/overload of a different size from any other male conductive element socket on the positive temperature coefficient of resistance resistor/overload.

16. (Withdrawn) The method of Claim 11 further comprising making the sockets on the positive temperature coefficient of resistance resistor/overload device electrically isolated from adjoining conductive parts.
17. (Withdrawn) The method of Claim 11 further comprising securing the male conductive terminal to at least one plate by means of welding.
18. (Withdrawn) The method of Claim 11 further comprising securing the male conductive terminal to at least one plate by means of soldering.
19. (Withdrawn) The method of Claim 11 further comprising securing the male conductive terminal to at least one plate by means of adhesive bonding.
20. (Withdrawn) The method of Claim 11 further comprising cuttingly removing at least one male conductive terminal from at least one plate.
21. (Withdrawn) A method for disconnecting a positive temperature coefficient of resistance resistor/overload device from electrically conductive wires in a plug assembly, the method comprising:
 - disengaging a locking tab on a flexible arm on the plug assembly from an angle on the positive temperature coefficient of resistance resistor/overload device by flexing the arm until the locking tab is released from under the angle;
 - disengaging the plug assembly from at least one socket containing a male conductive element on a positive temperature coefficient of resistance resistor/overload device; and
 - completely disconnecting the plug assembly from the positive temperature coefficient of resistance resistor/overload device such that no electrical

connection continues to exist between the plug assembly and the positive temperature coefficient of resistance resistor/overload device.